

TECHNICAL DATA

Fluke 301C



Key features

- The body weighs only 132g and is 16mm thick, which is light and portable and can be fitted into a pocket
- The slim and thin jaw of only 10mm can easily clamp onto tightly packed wires
- Tests AC voltage and current with the True-rms function.
- 1000A AC range, 0.01A high resolution
- Tests voltage, resistance and continuity
- Tests current frequency and voltage frequency
- Tests capacitance and diodes
- Backlight

Product overview: Fluke 301C

Fluke 301C

The Fluke 301C Clamp Meter has a lightweight and compact body, which allows you to carry it around in your pocket. The slim and thin jaw can easily clamp onto tightly packed wires. The Fluke 301C tests current, voltage, resistance, continuity, frequency (voltage and current), capacitance, and diode, etc.. You can handle more test needs with it. With the True-rms function, you can test complex signals more accurately, such as frequency conversion signals.

Specifications: Fluke 301C

Specifications

Accuracy is specified for 1 year after calibration, with operating temperatures from 18 °C to 28 °C and relative humidity from 0 % to 75 %. Accuracy specifications take the form of: \pm (% of Reading) + [Number of Least Significant Digits].

Models		301A/301A+		301B		301C		
AC Current (45 to 400 Hz)	Range	40.00 A	400.0 A	60.00 A	600.0 A	60.00 A	600.0 A	1000 A
	Resolution	0.01 A	0.1 A	0.01 A	0.1 A	0.01 A	0.1 A	1 A
	Accuracy	2 % + 10	2 % + 5	2 % + 10	2 % + 5	2 % + 10	2 % + 5	2 % + 5
AC Voltage (45 to 400 Hz)	Range	600.0 V		600.0 V		600.0 V		
	Resolution	0.1 V		0.1 V		0.1V		
	Accuracy	1.5% + 5		1.5% + 5		1.5% + 5		
DC Voltage	Range	600.0 V		600.0 V		600.0 V		
	Resolution	0.1 V		0.1 V		0.1 V		
	Accuracy	1% + 5		1% + 5		1% + 5		
Resistance	Range	600.0 Ω 6.000 k Ω 60.00 k Ω		600.0 Ω 6.000 k Ω 60.00 k Ω		600.0 Ω 6.000 k Ω 60.00 k Ω		
	Accuracy	1% + 5		1% + 5		1% + 5		
Voltage Frequency	Range	9.999 Hz 99.99 Hz 999.9 Hz 9.999 kHz 99.99 kHz		9.999 Hz 99.99 Hz 999.9 Hz 9.999 kHz 99.99 kHz		9.999 Hz 99.99 Hz 999.9 Hz 9.999 kHz 99.99 kHz		
	Accuracy	0.1% + 3		0.1% + 3		0.1% + 3		
Current Frequency	Range	45.0 to 400.0 Hz		45.0 to 400.0 Hz		45.0 to 400.0 Hz		
	Accuracy	0.1% + 3		0.1% + 3		0.1% + 3		
Capacitance	Range	9.999 μ F	99.99 μ F 999.9 μ F	9.999 μ F	99.99 μ F 999.9 μ F	9.999 μ F	99.99 μ F 999.9 μ F	
	Accuracy	2 % + 5	5% + 5	2 % + 5	5% + 5	2 % + 5	5% + 5	
Diode	Range	3.000 V		3.000 V		3.000 V		
	Accuracy	10%		10%		10%		
T-rms Value			-		-		☒	
Continuity			☒		☒		☒	
Hold			☒		☒		☒	
Backlight			-		☒		☒	
Safety rating			CAT III 300V		CAT III 300V		CAT III 300V	
Weight			132 g		132 g		132 g	
Size			190 mm x 52 mm x 16 mm		190 mm x 52 mm x 16 mm		190 mm x 52 mm x 16 mm	
Jaw Opening			34 mm		34 mm		34 mm	

Clamp Arm Size	10 mm X 10 mm	10 mm X 10 mm	10 mm X 10 mm
Battery	(2) AAA Batteries	(2) AAA Batteries	(2) AAA Batteries
Warranty	1 year	1 year	1 year
General Specifications			
Maximum Voltage between any Terminal and Earth Ground	300 V		
Maximum Differential Voltage between V/ Ω and COM Terminals	600 V		
Display (LCD)	6000 counts, updates 3 times per second		
Battery Type	2 AAA, IEC LR03		
Battery Life	500 hours minimum		
Auto Power Off Time	20 minutes		
Temperature	Operating: -10 °C to 50 °C		
	Storage: -30 °C to 60 °C		
Relative Humidity	Operating Humidity: Non condensing (<10°C); ≤ 90 % RH at 10 °C to 30 °C; ≤ 75 % RH at 30 °C to 40 °C; ≤ 45 % RH at 40 °C to 50 °C;		
Altitude	Operating: 2000 m; Storage: 12000 m		
Temperature Coefficient	0.1 x (specified accuracy) /°C (<18 °C or>28 °C)		
Dimensions (H x W x L)	190 mm x 52 mm x 16 mm		
Weight	132 g		
Jaw Opening	34 mm		
Ingress Protection Rating	IP30		
Safety	IEC 61010--1, IEC61010-2-032 CAT III 300 V, Pollution Degree 2		
Electromagnetic Environment	IEC 61326--1: Portable		

Ordering information



Fluke 301C

Models: Fluke 301C True-rms Clamp Meter

Fluke 301C

- Fluke 301C Clamp Meter
 - TL75 test lead
 - (2) AAA batteries
-

Fluke. Keeping your world up and running.®

Authorised Distributor:



46, Jalan SS 22/21, Damansara Jaya,
47400 Petaling Jaya,
Selangor Darul Ehsan, Malaysia.

*Email: ampmech@ampmech.com
Website: www.ampmech.com*

©2023 Fluke Corporation. Specifications subject to
change without notice.
12/2023

**Modification of this document is not permitted
without written permission from Fluke Corporation.**