


# Rittal – The System.

Faster – better – everywhere.



## AE 1008.600

## Compact enclosures AE

☒: 08/11/2022 (☒: [rittal.com/com-en](http://rittal.com/com-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# AE 1008.600 - Compact enclosures AE Stainless steel

Compact enclosure AE in stainless steel including mounting plate.



Model No.	AE 1008.600
Product modification	From August 2016, surface grinding will change from grain size 240 to grain size 400. The visually refined grinding finish will also enhance the enclosure's cleaning properties.
Material	Enclosure: Stainless steel Door: Stainless steel, all-round foamed-in PU seal Mounting plate: Sheet steel Stainless steel 1.4301 (AISI 304)
Surface finish	Enclosure and door: Brushed, grain 400, peak-to-valley height < 0.8 µm Mounting plate: Zinc-plated
Supply includes	Enclosure with door(s) Mounting plate Lock: 3 mm double-bit
Standard	NEMA 4X
Protection category to IEC 60 529	IP 66
IK Code	IK08
Dimensions	Width: 380 mm Height: 600 mm Depth: 210 mm
Mounting plate	Width: 334 mm Height: 570 mm
Number of doors	1
Number of locks	2
Lock	Lock version: Cam Number locks: 2 Lock insert: 3 mm double-bit Material lock: Die-cast zinc, nickel-plated




---

Basic material	Stainless steel
Packs of	1 pc(s).
Weight/pack	15.1 kg
Copper weight (kg per piece)	0
Customs tariff number	94032080
EAN	4028177000315
ETIM 7.0	EC000261
ECLASS 8.0	27180101



---

	DNV-GL GOST Lloyds Register of Shipping RRR UL + C-UL (listed)
	Declaration of conformity



Stainless steel enclosure (compact enclosure);  
protection category IP 66

**Enclosure:**

Made from 1.4301 (V2A) 1.25 or 1.5 mm stainless steel.  
Folded and welded from a single piece with protection  
channel around the door opening.

**Doors:**

1.5 or 2 mm 1.4301 stainless steel, flush-mounted, with  
foamed-in seal, concealed hinges, 130° opening angle as  
per VDI, cam lock with double-bit insert as per DIN  
43668.

**Mounting plate:**

2 - 3 mm sheet steel with system punchings,  
depth-adjustable stud mountings, zinc-plated.

**Accessories:**

Locking systems, earthing straps, wiring plan pockets,  
door stay, heat exchangers,  
fan-and-filter units, heaters, viewing window, panels

**Surface finish:**

Brushed

Dimensions (W x H x D): 380 x 600 x 210 mm

**Authorised Distributor:**



46, Jalan SS 22/21, Damansara Jaya,  
47400 Petaling Jaya,  
Selangor Darul Ehsan, Malaysia.

Email: [ampmech@ampmech.com](mailto:ampmech@ampmech.com)

Website: [www.ampmech.com](http://www.ampmech.com)