JACOBY•TARBOX®
A PRODUCT OF CLARK-RELIANCE

High Pressure Threaded Sight Flow Indicators

ASME Class 300, 600, 900, 1500

Section: T100
Bulletin: T100.15
Date: 10/2026
Supersedes: 1/2024

Jacoby-Tarbox's Full ASME rated line of high pressure threaded bulls-eye sight flow indicators are engineered per the design criteria of ASME B31.1 & B31.3, Power and Process Piping Codes, incorporating the listed ASTM materials for all metals in the unit construction.

"Out-of-the-box Compliance"

ASME B31.1 & B31.3
CRN – All Provinces
API 614
NACE MR0175 / ISO15156-1 MRO103*
PED (Specify when ordering for proper tagging)

*All Wetted Metals



Process View Maximized

View matches or exceeds pipe inside diameter, allowing 100% unobstructed process observation of liquids, slurries, gases and solids.

Minimal Pressure Drop

Non-rotor models have unrestricted flow as all internal openings are no smaller than the pipe's inside diameter.

Safely View process properties such as color, clarity, air entrainment, and interface.

Economically View drain, lube, hydraulic, condensate, food and return lines.

Standard Features:

- Single window tempered borosilicate (1 per side / 2 total)
- Cast Body
- 100% Hydrotest (See schedule T100.35)

Window and Shield Options:

- FM Approved dual window tempered borosilicate (2 per side / 4 total)
- UniShield® Window Protection - bonded PFA shielding for chemical resistance
- UniGlas® fused safety windows*

* ***Over 35 years without a single failure – ask us for details.***

	Plain 	Flapper 	Rotor 	Drip 	Gas Indicator 
Class 300	S-100HPA-CL3(NF)	S-100HPA-CL3	S-300HPA-CL3	S-200HPA-CL3	S-100HPA-CL3-GI
Class 600	S-100HPA-CL6(NF)	S-100HPA-CL6	S-300HPA-CL6	S-200HPA-CL6	S-100HPA-CL6-GI
Class 900	S-100HPA-CL9(NF)	S-100HPA-CL9	S-300HPA-CL9	S-200HPA-CL9	S-100HPA-CL9-GI
Class 1500	S-100HPA-CL15(NF)	Not Available	S-300HPA-CL15	S-200HPA-CL15	S-100HPA-CL15-GI
Indicator	None	316 Weighted Flapper with 316 Pin	PTFE Rotor with 316 Pin	316 Drip Tube	Light Weight PTFE Indicator with 316 Mount
Flow	Bi-Directional ⟷	Uni-Directional ←	Bi-Directional ⟷	Uni-Directional ←	Uni-Directional ←
Orientation	Horizontal or Vertical ✥	Horizontal or Vertical Upward ⊥	Horizontal or Vertical ✥	Vertical Downward or Horizontal ⊤	Horizontal or Vertical Upward ⊥
Application	Observe presence or absence of fluid	Flow changes by flapper position	Indicates relative process velocity by rotation speed	Condensing gasses (drip) or partially full liquid lines	Gas flows. Low velocity liquid flow in full lines

16633 Foltz Parkway ● Strongsville, OH 44149 USA
Telephone: +1 440- 572-1500 ● Fax: +1 440-238-8828
www.clarkreliance.com ● jacobytarbox@clarkreliance.com ● parts.clarkreliance.com

JACOBY·TARBOX®
A PRODUCT OF CLARK-RELIANCE

Part Number Matrix

High Pressure Threaded Sight Flow Indicators

CLASS 300 MODELS Up 750 psig (51.7 Bar) — Draw ing T400.117	
Model	Code
S-100HPA-CL3(NF)	TAZ
S-100HPA-CL3	TAZ
S-200HPA-CL3	TEZ
S-300HPA-CL3	TMZ
S-100HPA-CL3-DW(NF)	TYA
S-100HPA-CL3-DW	TYA
S-200HPA-CL3-DW	TYE
S-300HPA-CL3-DW	TYM

CLASS 600 MODELS Up 1500 psig (103 Bar) — Draw ing T400.118	
Model	Code
S-100HPA-CL6(NF)	TBZ
S-100HPA-CL6	TBZ
S-200HPA-CL6	TFZ
S-300HPA-CL6	TNZ
S-100HPA-CL6-DW(NF)	TYB
S-100HPA-CL6-DW	TYB
S-200HPA-CL6-DW	TYF
S-300HPA-CL6-DW	TYN

CLASS 900 MODELS Up 2250 psig (155 Bar) — Draw ing T400.119	
Model	Code
S-100HPA-CL9(NF)	TCZ
S-100HPA-CL9	TCZ
S-200HPA-CL9	TGZ
S-300HPA-CL9	TOZ
S-100HPA-CL9-DW(NF)	TYC
S-100HPA-CL9-DW	TYC
S-200HPA-CL9-DW	TYG
S-300HPA-CL9-DW	TYO

CLASS 1500 MODELS Up 3750 psig (258 Bar) — Draw ing T400.120	
Model	Code
S-100HPA-CL15(NF)	TDZ
S-200HPA-CL15	THZ
S-300HPA-CL15	TPZ
S-100HPA-CL15-DW(NF)	TYD
S-100HPA-CL15-DW	TYD
S-200HPA-CL15-DW	TYH
S-300HPA-CL15-DW	TYP

CODES: Model | Size | Wetted Metal | Body | Indicator | Window | Gasket | Non-Wetted | Faceplate

Size	Code
1/4"	04
3/8"	06
1/2"	08
3/4"	10
1"	12
1 1/2"	16
2"	18

Faceplate	Code
Jacoby-Tarbox	1

Material Note:
"Window Material", "Trim Material", and for Quartz, "Gasket Material", must be coordinated.

Match Designation
" T " = Tempered
" Q " = Quartz
" U " = UniGlas®

*Only use number in code

Trim Material	Code	
Carbon Steel (T-Boro Window)	1	T
316 SS (T-Boro Window)	2	T
Carbon Steel (Quartz Window)	4	Q
316 SS (Quartz Window)	5	Q
Carbon Steel (UniGlas Window)	6	U
316 SS (UniGlas Window)	7	U

Note: All steel trim limited to 600F (277C)

Body Material	(Max Temp)	Code
Carbon Steel (WCB)	(1000F/537C)	C
316 SS (CF8M)	(1500F/815C)	S
Bronze (B61)	(450F/232C)	B
316L SS (CF3M)	(1500F/815C)	6
Hastelloy® C (CW12MW)	(1300F/704C)	H
Alloy 20 (CN7M)	(600F/577C)	A
Monel® (M-35-1)	(900F/482C)	M
Duplex SS	Consult Factory	Code

Consult factory for special requirements.

Gasket choices for:
ALL Class 300 (CL3) & Class 600 (CL6)

Gasket Material	(Max Temp)	Code	
Neoprene	(250F/121C)	1	
Gylon® 3545	(500F/260C)	2	
Fiber (IFG® 5500)	(550F/287C)	3	
Graphite	(>800F/426C)	4	Q
FKM (Viton®)	(400F/204C)	5	

Gasket choices for:
ALL Class 900 (CL9) & Class 1500 (CL15)

Gasket Material	(Max Temp)	Code	
Neoprene - Not Available		~~1~~	
Gylon® 3545	(500F/260C)	2	
Fiber (IFG® 5500)	(550F/287C)	3	
Graphite	(>800F/426C)	4	Q
Viton - Not Available		~~5~~	

Body Machining	Code
Standard NPT	1
Optional Buttweld End	2
Optional Socket Weld End	3

Indicator Choices for 100's & 200's	Code
No Flapper = Plain (100 only) 316SS	0
Flapper (100) / 316 Drip (200)*	1
PTFE Flutter (100)	2
Gas Indicator	G

*Not available in CL15

Indicator Choices for 300's	Code
Standard PTFE Rotor	1
316SS Rotor - Note: ONLY use when PTFE is not comapatible with process or temperature exceeds 500F (260C)	2

Window Material	(Max Temp)	Code	
Tempered Boro Glass	(500F/260C)	1	T
T-Boro with UniShield®	(500F/260C)	2	T
Quartz Glass	(2012F/1100C)	4	Q
UniGlas® w/ Steel Ring	(600F/315C)	5	U
UniGlas® w/ Hast C Ring	(600F/315C)	6	U
UniGlas® w/ Duplex SS Ring	(532F/277C)	9	U

Rating Notes:
Design Temperature: Unit Temperature rating based on the lowest "Max Temperature" of selected components (ie. body, glass, gaskets)
Design Pressure: Actual Unit Pressure rating based on body material as defined by ASME B16.5 material group.

Authorised Distributor:
AMPMECH
46, Jalan SS 22/21, Damansara Jaya, 47400 Petaling Jaya, Selangor Darul Ehsan, Malaysia.
Email: ampmech@ampmech.com *Website: www.ampmech.com*